


[Home](#) | [Login](#) | [Logout](#) | [Access Information](#) | [Alerts](#) | [Purchase History](#) |

Welcome United States Patent and Trademark Office

Search Results[BROWSE](#)[SEARCH](#)[IEEE XPLORE GUIDE](#)

Results for "((((vlan policy)<in>metadata) <and> ((mac)<in>metadata))<and> ((authen..."

Your search matched **0** of **2365861** documents.A maximum of **100** results are displayed, **25** to a page, sorted by **Relevance** in **Descending** order.[» Search Options](#)[View Session History](#)[New Search](#)[» Key](#)

IEEE JNL IEEE Journal or Magazine

IET JNL IET Journal or Magazine

AIP JNL AIP Journal

AVS JNL AVS Journal

IEEE CNF IEEE Conference Proceeding

IET CNF IET Conference Proceeding

IEEE STD IEEE Standard



Indicates open access content

Modify Search

((((vlan policy)<in>metadata) <and> ((mac)<in>metadata))<and> ((authentication

☐ Check to search only within this results setDisplay Format: ☒ Citation ☐ Citation & Abstract[IEEE/ET/AIP/AVS](#)[Books](#)[Educational Courses](#)[A](#)

IEEE/ET journals, transactions, letters, magazines, conference proceedings, AIP/standards.


[view selected items](#)[Select All](#) [Deselect All](#)**No results were found.**

Please edit your search criteria and try again. Refer to the Help pages if you need assistance.

[Help](#) [Contact Us](#)

© Copyright 2009

Indexed by



Web Images Videos Maps News Shopping Gmail more ▾

Sign in

Google scholar

MAC address authentication before OR once

Search

Advanced Scholar Search
Scholar Preferences

☒ Search only in Engineering, Computer Science, and Mathematics.

☐ Search in all subject areas.

Scholar

Articles excluding patents ▾

1990

- 2003

include citations ▾

Results 1 - 10 of about

[PDF] Secure wireless internet access in public places

P Bahl, A Balachandran, S Venkatachary - Proc. IEEE ICC'01, 2001 - CiteSeer

... We noticed that the 100 Mb/sec backbone link gets saturated **before** the Verifier does. ... isolated on a "non-connected" **VLAN** until the **user** at that port is **authenticated** [21]. ... relies on an expensive specialized hardware **switch**, and is not secure from **MAC-address** spoofing attacks. ...

Cited by 29 - Related articles - View as HTML - All 17 versions

[PDF] Access control in an operator neutral public access network

M Hedenfalk - Proyecto Final de Carrera, Royal Institute of ..., 2002 - tslab.ssvi.kth.se

... 33 5.2.1 IP and **MAC address** spoofing The development of Diameter was needed to **address** several flaws in the design of the RADIUS protocol. These flaws include: ... The authenticator (the entity that wishes to enforce **authentication before** allowing access ...

Cited by 17 - Related articles - View as HTML - All 2 versions

An access control architecture for microcellular wireless IPv6 networks

S Schmid, J Finney, M Wu, A ... - CONFERENCE ..., 2001 - doi.ieeecomputersociety.org

... To prevent **MAC address** spoofing and replay attacks based on a spied access token, we encrypt the ... to obtain access to a **switch** LAN by means of the extensible **authentication** protocol (EAP ... The systems described above are all limited to **address** a single aspect, namely access ...

Cited by 13 - Related articles - BL Direct - All 13 versions

[PDF] The CHOICE network--broadband wireless Internet access in public places

P Bahl, A Balachandran, S Venkatachary - Microsoft Research, 2000 - CiteSeer

... not available in Windows 95, Windows 98, Windows CE, and several versions of **MAC OS**. ... Any packet with a destination **address** other than the DHCP server, the DNS server, the Web ... Upon **authentication** (by MS Passport), the PANS Authorizer does a look-up in its Policy Table ...

Cited by 16 - Related articles - View as HTML - All 6 versions

Network layer access control for context-aware IPv6 applications

A Friday, M Wu, J Finney, S Schmid, K Cheverst, N ... - Wireless Networks, 2003 - Springer

... port (the only host and port the mo- bile is allowed to communicate with **before** it has ... More advanced systems attempt to tackle one or more of the problems associated with **MAC address** filtering by ... Improving the performance of client **authentication** is the subject of future work. ...

Cited by 13 - Related articles - BL Direct - All 3 versions

[PDF] Making IEEE 802.11 Networks Enterprise-Ready

A Ayyagari, T Fout - White Paper, Microsoft Corporation, 2001 - CiteSeer

... easier to administer in large network environments than the currently used **MAC address** identification mechanism ... long duration, the IV is changed periodically; as frequently as every **MAC** protocol data ... a WEP shared key, the NIC should revert to the open system **authentication**. ...

Cited by 8 - Related articles - View as HTML - All 6 versions

[PDF] Applying the OSI seven layer network model to information security

D Reed - Practical GSEC, 2003 - mut.ac.th

... Built-in encryption, **authentication**, and **MAC** filtering may be applied to secure ... Vulnerabilities

Route spoofing - propagation of false network topology IP **Address** Spoofing- false ... Session Layer Vulnerabilities Weak or non-existent **authentication** mechanisms Passing of session ...

[Cited by 5](#) - [Related articles](#) - [View as HTML](#) - [All 4 versions](#)

[PDF] Building a secure Ethernet environment

F Prendergast, N Andover - PLANT ENGINEERING-CHICAGO ..., 2003 - siemens.com.ar

... In both cases, some providers offer add-on software and hardware modules for remote **authentication** and ... This acts to hide the original internal **address** of the sender inside the firewall. Firewalls allow filtering on **MAC** addresses, IP addresses, port numbers or even certain ...

[Cited by 1](#) - [Related articles](#) - [View as HTML](#) - [BL Direct](#)

[CITATION] Authenticated VLANs: Secure Network Access at Layer 2

J Hayes, J Thomas - Alcatel Telecommunications Review, 2002 - ALCATEL

[BL Direct](#) - [All 3 versions](#)

Custom solutions for complex networks

GM Whalley, DJ Newson, K Linseil, MJ Palmer - BT Technology Journal, 2000 - Springer

... force the issues to the attention of the network **user**, owner and designer sooner than ever **before**. ... into multiple logical switches, each consisting of a set of ports and the **MAC** addresses of ... ability of services such as dynamic DNS to cope with changes of IP **address**, • they allow ...

[Cited by 3](#) - [Related articles](#) - [BL Direct](#) - [All 5 versions](#)

Google 

Result Page: [1](#) [2](#) [3](#) [4](#) [5](#) [Next](#)

[Go to Google Home](#) - [About Google](#) - [About Google Scholar](#)

©2010 Google

[Web](#) [Images](#) [Videos](#) [Maps](#) [News](#) [Shopping](#) [Gmail](#) [more ▾](#)

[Sign in](#)

Google scholar [Advanced Scholar Search](#)
[Scholar Preferences](#)

☒ Search only in Engineering, Computer Science, and Mathematics.
☐ Search in all subject areas.

Scholar - Results **1 - 10** of about

Did you mean: MAC address **authentication** user password switch OR multi-layer OR multi-tier "layer 2"

[PDF] [Design and implementation of a WLAN/CDMA2000 interworking architecture](#)

... , G Chandranmenon, S Han, YW Lee ... - IEEE ... , 2003 - [cchen1.csie.ntust.edu.tw](#)

... 2, 3 and 7. The model relies on the dynamic packet fil- ters that use information that includes **MAC address**, IP source and destination **address**, and TCP ... In our model, a non-802.11i mobile node can connect through the access point without any **layer-2 authentication**. ...

[Cited by 178](#) - [Related articles](#) - [BL Direct](#) - [All 15 versions](#)

[PDF] [Integration of 802.11 and third-generation wireless data networks](#)

M Buddhikot, G Chandranmenon, SJ Han, YW Lee, S ... - IEEE INFOCOM, 2003 - [Citeseer](#)

... accounting subsystem also obtains auxiliary information such as **user** identity, **IP address**, **MAC address**, etc. ... However, it does not support seamless mobility, and requires manual **user** intervention to **switch** ... In this service, a session is **authenticated** via a web browser, while local ...

[Cited by 266](#) - [Related articles](#) - [View as HTML](#) - [BL Direct](#) - [All 39 versions](#)

[PDF] [Secure wireless internet access in public places](#)

P Bahl, A Balachandran, S Venkatachary - Proc. IEEE ICC'01, 2001 - [Citeseer](#)

... NetBar system is yet another proposal in which a NetBar port remains isolated on a "non-connected" VLAN until the **user** at that port is **authenticated** [21]. This system relies on an expensive specialized hardware **switch**, and is not secure from **MAC-address** spoofing attacks. ...

[Cited by 29](#) - [Related articles](#) - [View as HTML](#) - [All 17 versions](#)

[Virtual operator based AAA in wireless LAN hot spots with ad-hoc networking ...](#)

J Zhang, J Li, S Weinstein, N Tu - ACM SIGMOBILE Mobile ... , 2002 - [portal.acm.org](#)

... rely on **MAC address** or **IP address** based access control, which are obviously quite vulnerable given that **MAC** addresses and ... If somebody fakes the source **IP address** in the packet without knowing the shared key, the IP packet headers will ... IV.A.1. The **authentication** procedure ...

[Cited by 25](#) - [Related articles](#) - [All 2 versions](#)

[PDF] [The CHOICE network—broadband wireless Internet access in public places](#)

P Bahl, A Balachandran, S Venkatachary - Microsoft Research, 2000 - [Citeseer](#)

... not available in Windows 95, Windows 98, Windows CE, and several versions of **MAC OS**. ... there is an end-to-end secure channel between the **user** and the **authentication** service ... 3.2.2 **Address** Allocation and Naming The CHOICE network uses a standard DHCP server to lease ...

[Cited by 18](#) - [Related articles](#) - [View as HTML](#) - [All 6 versions](#)

[PDF] [On the establishment of an access VPN in broadband access networks](#)

R Cohen - IEEE Communications Magazine, 2003 - [Citeseer](#)

... **Authentication** and autho- rization can be performed either by the DHCP server, based on the host's **MAC address**, or after the host gets its initial ... In the sec- ond subcase the **user** is allowed to select an ISP and **switch** from one ISP to another using some online mechanism. ...

[Cited by 32](#) - [Related articles](#) - [View as HTML](#) - [BL Direct](#) - [All 6 versions](#)

An access control architecture for microcellular wireless IPv6 networks

S Schmid, J Finney, M Wu, A ... - CONFERENCE ..., 2001 - doi.ieeecomputersociety.org

... To prevent **MAC address** spoofing and replay attacks based on a spied access token, we ... by external nodes based on packet analysis (ie, packet type, source **address**, data rate, etc ... dynamically enable or disable link- layer access to network ports based on **user authentication**. ...

[Cited by 13](#) - [Related articles](#) - [BL Direct](#) - [All 13 versions](#)

Network layer access control for context-aware IPv6 applications

A Friday, M Wu, J Finney, S Schmid, K Cheverst, N ... - Wireless Networks, 2003 - Springer

... this method authorizes a terminal to have access to the network, not the **user** in possession ... advanced systems attempt to tackle one or more of the problems associated with **MAC address** filtering by ... Improving the performance of client **authentication** is the subject of future work. ...

[Cited by 13](#) - [Related articles](#) - [BL Direct](#) - [All 9 versions](#)

[PDF] Access control in an operator neutral public access network

M Hedenfalk - Proyecto Final de Carrera, Royal Institute of ..., 2002 - islab.ssvi.kth.se

... 33 5.2.1 IP and **MAC address** spoofing The system should allow for assigning publically routable IP **address** to the users, ie, not only private **address** combined with network **address** translation (NAT ... The session between client and server is **authenticated** using a shared secret ...

[Cited by 17](#) - [Related articles](#) - [View as HTML](#) - [All 2 versions](#)

[PDF] Making IEEE 802.11 Networks Enterprise-Ready

A Ayyagari, T Fout - White Paper, Microsoft Corporation, 2001 - Citeseer

... easier to administer in large network environments than the currently used **MAC address** identification mechanism ... long duration, the IV is changed periodically; as frequently as every **MAC** protocol data ... a WEP shared key, the NIC should revert to the open system **authentication**. ...

[Cited by 8](#) - [Related articles](#) - [View as HTML](#) - [All 6 versions](#)

Did you mean to search for: MAC address **authentication** user password switch OR multi-layer OR multi-tier "layer 2"

Google

Result Page: 1 2 3 4 5 6 7 8 9 10 **Next**

MAC address authenticated user pa Search

[Go to Google Home](#) - [About Google](#) - [About Google Scholar](#)

©2010 Google